

SAFETY DATA SHEET

JAX BATTERY SAVER (AEROSOL)

Infosafe No.:LQ3VG
Version No.:1.0
ISSUED Date:22/10/2014
ISSUED BY Industrial Lubricants &
Services Ltd

CLASSIFIED AS HAZARDOUS

1. IDENTIFICATION

GHS Product Identifier

JAX BATTERY SAVER (AEROSOL)

Company Name

Industrial Lubricants & Services Ltd

Address

PO Box 259 347, Botany, Manukau 2163
Auckland, New Zealand

Telephone/Fax Number

Tel: 0800 10 40 11

Fax: 0800 10 40 15

Emergency phone number

0800 10 40 17

E-mail Address

orders@industlubes.co.nz

Recommended use of the chemical and restrictions on use

Lubricant where there is no possibility of contact with food.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

HSNO Classification:

2.1.2A - Flammable aerosols (1)

6.3B - Substance that is mildly irritating to the skin

9.1B - Substance that is toxic in the aquatic environment

Signal Word (s)

DANGER

Hazard Statement (s)

H222 Extremely flammable aerosol.

H316 Causes mild skin irritation.

H411 Toxic to aquatic life with long lasting effects.

Pictogram (s)

Flame, Environment

**Precautionary statement – Prevention**

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces, No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P273 Avoid release to the environment.

Precautionary statement – Response

GENERAL

P391 Collect spillage.

SKIN

P332+P313 If skin irritation occurs: Get medical advice/ attention.

Precautionary statement – Storage

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Precautionary statement – Disposal

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Information on Composition

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) contain less than 0.1% w/w benzene (EC no. 200-753-7)

Ingredients

Name	CAS	Proportion	Hazard	Hazard Statement (s)
Propane	74-98-6	10-25 %		
Naphtha (petroleum), hydrotreated light	64742-49-0	10-25 %		
Butane	106-97-8	10-25 %		
Amines, C12-14-tert-alkyl	68955-53-3	<2.5 %		
Ingredients determined not to be hazardous		Balance		

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

Ingestion

Unlikely to occur due to the physical state of the product. However, if ingested, rinse mouth with water. Do NOT induce vomiting. Seek medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and/or persist seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (New Zealand 0800 POISON / 0800 764 766) or a doctor at once.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide, sand, dry chemical, foam, water fog or water mist.

Unsuitable Extinguishing Media

Water jet

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific Hazards Arising From The Chemical

Contents under pressure - cans can explode in a fire or may become a projectile in a fire. This product is extremely flammable. Keep containers and fire-exposed surfaces cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard. May be sensitive to static discharge. Aerosols are sensitive to mechanical impact.

Hazchem Code

2YE

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Extinguish or remove all sources of ignition. Wear appropriate personal protective equipment and clothing to prevent exposure. Evacuate all unprotected personnel. Water spray or fog may be used to disperse/absorb vapour if any. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Place inert, non-combustible absorbent material onto liquid spillage. Collect residues and seal in labelled drums for disposal. If contamination of sewers or waterways occurs inform the local water authorities and waste management authorities in accordance with local regulations. Dispose of waste according to applicable local and national regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

EXTREMELY FLAMMABLE. VAPOUR OR GAS REDUCES OXYGEN FOR BREATHING. IN CONFINED SPACES MAY CAUSE ASPHYXIATION. Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. DO NOT store or use in confined spaces. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Build up of mists or vapours in the atmosphere must be prevented. Do NOT cut or heat containers as they may contain hazardous residues. Do not smoke. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities. When sanding or abrading the dried film, wear a dust/mist respirator.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area away from sources of ignition, oxidising agents, foodstuffs, clothing and out of direct sunlight. Protect container against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Do NOT pressurise, cut or heat aerosol containers. Content is under pressure and can explode violently. For information on the design of the storeroom, reference should be made to Australian Standard AS 2278-2000 Non-refillable metal aerosol dispensers of capacity 50 mL to 1000 mL inclusive. Reference should also be made to all Local, State and Federal regulations.

Storage Temperatures

Do not store above 50°C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure value assigned for this material by Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, the available exposure limits for ingredients are listed below:

New Zealand Occupational Safety and Health Service (OSH) Workplace Exposure Standards:

Butane

TWA: 800 ppm

TWA: 1900 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Biological Limit Values

No biological limits allocated

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements. Refer to AS 2865 Australian Standard Safe working in a confined space, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Other Information

Propane and Butane are asphyxiant gases which when present in an atmosphere in high concentration, lead to reduction of oxygen concentration by displacement or dilution. It is not appropriate to recommend an exposure standard for an asphyxiant, rather it should be required that a sufficient oxygen concentration be maintained.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Black aerosol

Colour

Black

Odour

Ether like

Decomposition Temperature

Not available

Melting Point

Not available

Boiling Point

Not available

Solubility in Water

Not available

pH

Not available

Vapour Pressure

Not available

Vapour Density (Air=1)

Not available

Evaporation Rate

Not available

Odour Threshold

Not available

Viscosity

Not available

Partition Coefficient: n-octanol/water

Not available

Density

0.80-0.82 g/cm³ (20°C) (Concentrate)

Flash Point

Not available

Flammability

Extremely flammable aerosol

Auto-Ignition Temperature

Not available

Flammable Limits - Lower

Not available

Flammable Limits - Upper

Not available

Explosion Properties

No explosion hazard

10. STABILITY AND REACTIVITY

Reactivity

Reacts with incompatible materials.

Chemical Stability

Stable under normal conditions of storage and handling.

Conditions to Avoid

Heat, direct sunlight, flames and other sources of ignition.

Incompatible materials

Strong oxidizing agents, acids and alkalis.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: carbon monoxide and carbon dioxide.

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material. The available toxicity data for ingredients given below.

Acute Toxicity - Inhalation

Butane

LC50(rat): 658mg/l/4h

Ingestion

Unlikely due to form of product. Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin

Causes mild skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

May be irritating to eyes. The symptoms may include redness, itching and tearing.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

Not expected to cause toxicity to a specific target organ.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Dispose of waste according to applicable local and national regulations. Do not cut, puncture or weld on or near containers. Empty containers may contain flammable residues. Empty the container completely before disposal. Contaminated containers must not be treated as household waste. Advise flammable nature. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

Product Disposal:

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a flammable substance contained in a pressurised container. Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.

Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected. In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Container Disposal:

Do not pierce, burn, cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Empty the container completely before disposal. Contaminated containers must not be treated as household waste. Advise flammable nature. In this instance the packaging can be disposed through a commercial waste collection service.

Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous. In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

14. TRANSPORT INFORMATION

Transport Information

Road and Rail Transport:

This material is classified as Dangerous Goods Division 2.1 Flammable Gases

Class 1: Explosives

Division 2.3: Toxic gases

Class 3: Flammable liquids

Division 4.2: Spontaneously combustible substances

Division 4.3: Dangerous when wet substances

Division 5.1: Oxidising substances

Division 5.2: Organic peroxides

Class 7: Radioactive materials unless specifically exempted

Must not be loaded in the same freight container; and on the same vehicle must be separated horizontally by at least 3 metres unless all but one are packed in separate freight containers with:

Division 4.1: Flammable Solids

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Proper Shipping Name: AEROSOLS (Naphtha (petroleum), hydrotreated light) MARINE POLLUTANT

UN-No: 1950

Division: 2.1

EmS: F-D,S-U

Special Provisions: 63, 190, 277, 327, 344, 959

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Proper Shipping Name: Aerosols,flammable

UN-No: 1950

Division: 2.1

Label: Flammable gas

Packaging Instructions (cargo only): 203

Packaging Instructions (passenger & cargo): 203

Special Provisions: A145, A167, A802

U.N. Number

1950

UN proper shipping name

AEROSOLS

Transport hazard class(es)

2.1

Hazchem Code

2YE

Special Precautions for User

Not available

EPG Number

2D1

IERG Number

49

IMDG Marine pollutant

Yes

Transport in Bulk

Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Group Standard: Aerosols (Flammable) Group Standard 2006..

HSNO Approval Number

HSR002515

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS Created: October 2014

References

Workplace Exposure Standards and Biological Exposure Indices, Department of Labour, Health & Safety.

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Assigning a hazardous substance to a group standard.

American Conference of Industrial Hygienists (ACGIH)

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.