

SAFETY DATA SHEET

JAX FGH-AW ISO 32, 46, 68, 100

Infosafe No.: LQ452
Version No.: 1.0
ISSUED Date: 06/01/2015
ISSUED BY Industrial Lubricants &
Services Ltd

1. IDENTIFICATION

GHS Product Identifier

JAX FGH-AW ISO 32, 46, 68, 100

Company Name

Industrial Lubricants & Services Ltd

Address

PO Box 259 347, Botany, Manukau 2163
Auckland, New Zealand

Telephone/Fax Number

Tel: 0800 10 40 11
Fax: 0800 10 40 15

Emergency phone number

0800 10 40 17

E-mail Address

orders@industlubes.co.nz

Recommended use of the chemical and restrictions on use

Lubricant.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Not classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Information on Composition

Contains <3% DMSO extract as measured by IP 346.

Ingredients

Name	CAS	Proportion
Lubricating Oil (Petroleum), Hydrotreated Neutral Oil Based	72623-86-0	50-100 %
Ingredients determined not to be hazardous		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek medical attention.

Skin

Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and/or persist seek medical attention.

First Aid Facilities

Eyewash and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (0800 764 766)

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use carbon dioxide, dry chemical, water spray or foam.

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific Hazards Arising From The Chemical

This product will burn if exposed to fire.

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene by washing hands prior to eating, drinking, smoking or using toilet facilities.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material, however, the TWA exposure standards for oil mist is 5 mg/m³. STEL:10 mg/m³ (mineral). As with all chemicals, exposure should be kept to the lowest possible levels.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Biological Limit Values

No biological limits allocated

Appropriate Engineering Controls

Provide sufficient ventilation to keep airborne levels below the exposure limits or as low as possible. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to relevant regulations for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Liquid

Appearance

Liquid

Colour

Water white.

Odour

Light odour

Decomposition Temperature

Not available

Melting Point

Not available

Boiling Point

Not available

Solubility in Water

Not available

pH

Not available

Vapour Pressure

Not available

Vapour Density (Air=1)

Not available

Evaporation Rate

Not available

Odour Threshold

Not available

Viscosity

Not available

Partition Coefficient: n-octanol/water

Not available

Density

0.86 g/cm³ at 20°C

Flash Point

204°C (ASTM D 92)

Flammability

Combustible liquid

Auto-Ignition Temperature

Not available

Flammable Limits - Lower

Not available

Flammable Limits - Upper

Not available

Explosion Properties

Product does not present an explosion hazard.

Oxidising Properties

Not available

10. STABILITY AND REACTIVITY

Reactivity

Reacts with incompatible materials.

Chemical Stability

Stable under normal conditions of storage and handling.

Conditions to Avoid

Heat, direct sunlight, flames and other sources of ignition. Direct sunlight.

Incompatible materials

Strong oxidizing agents. Strong alkalis and strong acids.

Hazardous Decomposition Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material. The available toxicity data for the ingredients are as follows:

Acute Toxicity - Oral

Lubricating Oil (Petroleum), Hydrotreated Neutral Oil Based:
LD50 (Rat): >5000 mg/kg

Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin

May be irritating to skin. The symptoms may include redness, itching and swelling.

Eye

May be irritating to eyes. The symptoms may include redness, itching and tearing.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

Not expected to cause toxicity to a specific target organ.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No ecological data available for this material.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Prevent this material entering waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

Product Disposal:

This product can be disposed through a licensed commercial waste collection service. This product is non-hazardous and therefore the New Zealand HSNO regulations regarding disposal do not apply, however other regulations may apply.

This product is a non-hazardous, combustible substance; It should be recycled whenever possible or sent to an approved high temperature incineration plant for disposal.

Container Disposal:

The product is non-hazardous, therefore, the packaging may be re-used or recycled if it has been treated to remove any residual contents of the substance. Any wash-off water from the container cleaning process should be sent to a suitable waste water treatment plant before discharge into the environment.

In New Zealand, the packaging (that may or may not contain any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of

compliance with regulations.

14. TRANSPORT INFORMATION

Transport Information

Not classified as Dangerous Goods for transport according to the NZS 5433:2012 Transport of Dangerous Goods on Land.

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

U.N. Number

None Allocated

UN proper shipping name

None Allocated

Transport hazard class(es)

None Allocated

IMDG Marine pollutant

No

15. REGULATORY INFORMATION

Regulatory information

Not classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS Created: January 2015

References

Workplace Exposure Standards and Biological Exposure Indices

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Assigning a hazardous substance to a group standard.

American Conference of Industrial Hygienists (ACGIH)

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.