



Ilocut 482

High performance neat cutting oil

Description

Castrol Ilocut™ 482 is a medium viscosity, chlorinated neat cutting oil.

Application

Ilocut 482 is designed for general machining, grinding and broaching of cast iron to high alloy steels and non-ferrous metals.

Advantages

- Advanced additive technology gives high extreme pressure (EP) lubricity properties and lowers production costs through extended tool life
- Improved surface finish and increased cutting speeds leads to improvement of process efficiency
- Multi-metal machining using our superior additive technology provides opportunity for product consolidation

Typical Characteristics

Name	Method	Units	Ilocut 482
Density @ 15°C, Relative	ASTM D1298	kg/m ³	882
Appearance	Visual	-	Clear & Bright amber oil
Viscosity @ 40°C	DIN 51562	mm ² /s	19
Flash Point, COC	ASTM D92	°C	198
Copper Corrosion, 3hrs @ 100°C	ASTM D130	Rating	1 b

Additional Information

	Cast Iron	Low-Medium Alloyed Steel	High Alloyed Steel/Nickel Chromium Alloys	Aluminium Alloys	Yellow Metals
Grinding	X	X	X	X	X
Drilling			X	X	X
Broaching/Gear Manufacturing	X	X		X	X
General Machining	X	X	X	X	X

Ilocut 482

25 Apr 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)
Technical Advice Line: 0800 10 40 60 / Customer Service: 0800 CASTROL (227 876)
<http://msdspd.castrol.com>