



Agri AS Trans Plus 20W-30

Universal, wet brake transmission/ hydraulic fluid

Description

Castrol Agri AS Trans Plus is a universal, wet brake transmission/ hydraulic fluid designed to satisfy the various requirements of most tractor and farm machinery manufacturers. The AS (anti-squawk) characteristics of the formulation help to minimise the effect of wet brake chatter.

Advantages

- One oil reduces inventory and saves money
- One oil simplifies servicing and avoids misapplication
- Formulated to minimise wet brake chatter and improve brake efficiency
- Provides outstanding gear wear protection and bearing durability extending component life

Typical Characteristics

Name	Method	Units	Agri AS Trans Plus 20W-30
Density @ 15C, Relative	ASTM D1298	g/ml	0.889
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	10.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	84
Viscosity Index	ASTM D2270	None	117
Viscosity, Brookfield @ -26C (80W)	ASTM D2983	mPa.s (cP)	31400
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	250

Product Performance Claims

API GL-4

Meets - MFM1135, Ford ESN-M2C-86B

Can be used where NH 420A is specified.

Agri AS Trans Plus 20W-30

19 Jul 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)
www.castrol.co.nz www.msds.castrol.co.nz