



## Iloform PN 223

Chlorine free vanishing oil

### Description

Castrol Iloform™ PN 223 is a low viscosity, chlorine and heavy metal free, metal stamping fluid. It is a blend of high lubricity boundary lubrication additives, in a low odour, dearomatised hydrocarbon.

### Application

Iloform PN 223 is specially formulated for use in light duty sheet stamping operations where very low residues are required, in most cases eliminating the need for inter process cleaning.

It is especially recommended for use in electrical steel stamping applications.

It is suitable for use on light gauge uncoated steels as well as zinc coated steels, and yellow metals.

### Advantages

- Excellent health, safety and environmental profile. Formulated on mild odour, very low aromatic dearomatised hydrocarbon and free from chlorinated and heavy metal containing constituents such as Barium.
- Contains high performance boundary lubricants which maximise punch life and provide excellent surface finish. Minimises costs associated with tool repolishing.
- Reliable short term corrosion protection minimises rework costs.
- Quick drying, low residue characteristics can eliminate requirements for inter process cleaning.
- Superior wetting provides thin, homogenous lubricating film.
- Low viscosity. Maximises flushing effect to aid removal of particulates from punches and dies, minimising component defects. Reduces drag out rates hence reduces product consumption.
- Low odour and improved working environment. Excellent operator acceptability.

## Typical Physical Characteristics

	Test Method	Unit	Value
Appearance	Visual	Visual	Clear colourless fluid
Viscosity @ 20°C	DIN 51 562	mm <sup>2</sup> /s	1.6
Density @ 15°C	DIN 51 757 / ASTM D 1298	kg/m <sup>3</sup>	770
Flash Point	ISO 2592	°C	62
Copper corrosion	DIN 51 759 T1 / ASTM D 130	3 h at 100°C	1a

Ester	Sulphur	Phosphorous	Chlorine	Other
✓				

Iloform PN 223

16 Mar 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)

Technical Advice Line: 0800 10 40 60 / Customer Service: 0800 CASTROL (227 876)

[www.castrol.co.nz](http://www.castrol.co.nz) [www.msds.castrol.co.nz](http://www.msds.castrol.co.nz)