



## Castrol EDGE Professional OE-X 5W-30

Unlock True Engine Performance

### Description

Advances in engine technology have led to increased power and efficiency, meaning engines work harder and under higher pressures than ever before. This means the oil has to be stronger to reduce friction and protect the engine.

Castrol EDGE Professional OE-X 5W-30 gives you the confidence to demand maximum engine performance from today's latest technology, highly engineered engines that operate with tighter tolerances, requiring lower viscosity oils.

Castrol EDGE Professional is micro-filtered and CO2 neutral according to the highest global standard\*. It provides the strength to help maximise your vehicles performance.

\* in accordance with the BSI PAS 2060 specification

### Application

Castrol EDGE Professional OE-X 5W-30 is an advanced full synthetic engine oil suitable for use in automotive petrol and diesel engines where the manufacturer recommends an ACEA C3 API SN/CF or earlier specification 5W-30 lubricant.

Suitable for many automotive diesel engines fitted with Diesel Particulate Filters (DPF).

Castrol EDGE Professional OE-X 5W-30 is approved by leading automobile manufacturers, please refer to the specifications section and your owners handbook.

\*GM dexos2®: supersedes GM-LL-B-025 and GM-LL-A-025 : GB2C1126082

### Advantages

Castrol EDGE Professional OE-X 5W-30:

- Maximises short and long term engine performance
- Reduces engine deposits to help maximise engine response
- Delivers complete protection across a variety of engine speeds, conditions and temperatures
- Sustains maximum performance even when under pressure
- Independently proven to improve engine efficiency
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- Delivers and sustains maximum horsepower for longer, even when under pressure
- Suitable for use in diesel engines that are equipped with a DPF

## Typical Characteristics

Name	Method	Units	Castrol EDGE Professional OE-X 5W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.852
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	12.4
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	6500
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	75
Viscosity Index	ASTM D2270	None	165
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	210
Ash, Sulphated	ASTM D874	% wt	0.8

## Product Performance Claims

ACEA C3  
API SN/CF  
GMdexos2™\*  
MB-Approval 229.31/ 229.51

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional OE-X 5W-30  
02 Jul 2019  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol NZ (a business division of BP Oil New Zealand Limited)  
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)  
www.castrol.co.nz www.msds.castrol.co.nz