



Spheerol™ BTX 2

Heavy Duty Grease

Description

Castrol Spheerol™ BTX 2 Grease (previously called BTX Grease) is a high performance grease developed for use in a wide range of mining and industrial applications.

Spheerol BTX Grease uses a unique combination of extreme pressure and antiwear agents, corrosion and oxidation inhibitors in a lithium complex base.

Application

Spheerol BTX Grease draws on field trial experience in a number of severely heavy duty applications including motorsport.

The formulation is engineered to provide outstanding protection of ball and rolling bearings in high speed and load applications. It is also suitable for general chassis greasing, ball joints, constant velocity joints and other sliding surfaces and plain bearing lubrication. It is also used in applications like Jack shafts, Bucket pins and Vibrating shafts.

Continuous Operating Temperature Range: -35°C to 175°C

Intermittent Operating Temperature Range: -40°C to 200°C

Advantages

- Combines excellent extreme pressure and adhesion properties with high temperature stability to outperform conventional unfortified greases.
- It has a very high drop point and is suitable for a wide range of operating temperatures.
- Water resistant and contains a powerful corrosion inhibitor to protect lubricated machinery parts under wet conditions. The high performance characteristics of the grease allow it to be recommended for the most arduous conditions.
- Engineered to maximise equipment durability in a diverse range of applications.

Typical Characteristics

| Name | Method | Units | |
|--------------------------------------|------------|--------------------|---------------------------|
| Appearance | Visual | - | Smooth green tacky grease |
| Base oil kinematic viscosity at 40°C | ISO 12058 | mm ² /s | 500 |
| Penetration, worked 60 Cycles | ASTM D217 | 1/10 mm | 275 - 295 |
| Dropping Point, Grease | ASTM D2265 | °C | 250 min |

Subject to usual manufacturing tolerances

Spheerol™ BTX 2

10 Jan 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 717 Bourke Street, Docklands Vic 3008

Technical Advice Line: 1300 557 998 Customer Service: 1300 722 088

<http://msdspd.castrol.com>